

class FB JSAPIImpl unregisterEventMethod (2)

- FireEvent
- FireEvent
- FireJSEvent
- FireJSEvent
- FireJSEvent
- getDefaultZone
- getZone
- invalidate
- JSAPIImpl
- popZone
- pushZone
- registerEvent
- registerEvent
- registerEventInterface
- registerEventMethod
- registerEventMethod
- setDefaultZone
- shutdown
- unregisterEventInterface
- ace
- unregisterEventMethod
- od
- unregisterEventMethod
- od
- ~JSAPIImpl

```
void FB::JSAPIImpl::unregisterEventMethod (const std::wstring & name,
                                           JSObjectPtr & event inlinevirtual
                                           )
```

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Reimplemented from `FB::JSAPI`.

Definition at line 292 of file `JSAPIImpl.h`.

References `unregisterEventMethod()`, and `FB::wstring_to_utf8()`.

```
293 {
294   unregisterEventMethod(wstring_to_utf8(name), event);
295 }
```

`FB::JSAPIImpl::unregisterEventMethod`

virtual void unregisterEventMethod(const std::string &name, JSObjectPtr &event)

Called by the browser to unregister an event handler method.

Definition: `JSAPIImpl.cpp:266`

`FB::wstring_to_utf8`

std::string wstring_to_utf8(const std::wstring &src)

Accepts a std::wstring and returns a UTF8-encoded std::string.

Definition: `utf8_tools.cpp:37`

Here is the call graph for this function:

