

class FB JSAPIAuto getMemberNames

- Construct
- FireJSEvent
- get_valid
- getAttribute
- getMemberCount
- getMemberNames**
- getMethodObject
- GetProperty
- GetProperty
- HasMethod
- HasMethodObject
- HasProperty
- HasProperty
- Invoke
- isReserved
- JSAPIAuto
- registerAttribute
- registerMethod
- registerProperty
- RemoveProperty
- RemoveProperty
- setAttribute
- SetProperty
- SetProperty
- setReserved
- ToString
- unregisterMethod
- unregisterProperty

```
void FB::JSAPIAuto::getMemberNames (std::vector< std::string > & nameVector) const virtual
```

Called by the browser to enumerate the members of this **JSAPI** object.

This must be implemented by anything extending **JSAPI** directly. **JSAPIAuto** implements this for you.

Parameters

[out] **nameVector** The name vector.

Implements **FB::JSAPI**.

Definition at line 125 of file **JSAPIAuto.cpp**.

```
126 {
127     boost::recursive_mutex::scoped_lock lock(m_zoneMutex);
128     nameVector.clear();
129     for (ZoneMap::const_iterator it = m_zoneMap.begin(); it != m_zoneMap.end();
++it) {
130         if (getZone() >= it->second)
131             nameVector.push_back(it->first);
132     }
133 }
```

FB::JSAPIImpl::getZone

virtual SecurityZone getZone() const
Gets the currently active zone.

Definition: [JSAPIImpl.h:238](#)