

# class FB JSAPI GetMethodObject

- Construct
- getDefaultZone
- getMemberCount
- getMemberNames
- GetMethodObject
- GetMethodObject
- GetProperty
- GetProperty
- GetProperty
- getZone
- HasMethod
- HasMethod
- HasMethodObject
- HasMethodObject
- HasProperty
- HasProperty
- HasProperty
- invalidate
- Invoke
- Invoke
- JSAPI
- popZone
- pushZone
- registerEventInterface
- registerEventMethod
- registerEventMethod
- RemoveProperty
- RemoveProperty
- RemoveProperty
- setDefaultZone
- SetProperty
- SetProperty
- SetProperty
- shutdown
- unregisterEventInterface
- unregisterEventMethod
- unregisterEventMethod
- ~JSAPI

```
JSAPIPtr FB::JSAPI::GetMethodObject ( const std::wstring & methodObjName ) inlinevirtual
```

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Definition at line 362 of file JSAPI.h.

References [FB::wstring\\_to\\_utf8\(\)](#).

```
363 {
364     return GetMethodObject ( FB::wstring_to_utf8 ( methodObjName ) );
365 }
FB::JSAPI::GetMethodObject
virtual JSAPIPtr GetMethodObject ( const std::wstring & methodObjName )
Definition: JSAPI.h:362
FB::wstring_to_utf8
std::string wstring_to_utf8 ( const std::wstring & src )
Accepts a std::wstring and returns a UTF8-encoded std::string.
Definition: utf8_tools.cpp:37
```

Here is the call graph for this function:

