

# class FB JSAPI RemoveProperty

- Construct
- getDefaultZone
- getMemberCount
- getMemberNames
- GetMethodObject
- GetMethodObject
- GetProperty
- GetProperty
- GetProperty
- getZone
- HasMethod
- HasMethod
- HasMethodObject
- HasMethodObject
- HasProperty
- HasProperty
- HasProperty
- invalidate
- Invoke
- Invoke
- JSAPI
- popZone
- pushZone
- registerEventInterface
- registerEventMethod
- registerEventMethod
- RemoveProperty**
- RemoveProperty
- RemoveProperty
- setDefaultZone
- SetProperty
- SetProperty
- SetProperty
- shutdown
- unregisterEventInterface
- unregisterEventMethod
- unregisterEventMethod
- ~JSAPI

variant FB::JSAPI::RemoveProperty(const std::wstring & propertyName) inlinevirtual

This is an overloaded member function, provided for convenience. It differs from the above function only in what argument(s) it accepts.

Reimplemented in [FB::JSAPIProxy](#).

Definition at line 455 of file [JSAPI.h](#).

References [FB::wstring\\_to\\_utf8\(\)](#).

Referenced by [FB::Npapi::NPObjectAPI::RemoveProperty\(\)](#).

```
456 {
457     return RemoveProperty(wstring_to_utf8(propertyName));
458 }
```

[FB::JSAPI::RemoveProperty](#)

virtual void RemoveProperty(const std::wstring &propertyName)

**Definition:** [JSAPI.h:455](#)

[FB::wstring\\_to\\_utf8](#)

std::string wstring\_to\_utf8(const std::wstring &src)

Accepts a std::wstring and returns a UTF8-encoded std::string.

**Definition:** [utf8\\_tools.cpp:37](#)

Here is the call graph for this function:

